

[54] ELECTRODE ASSEMBLY FOR SENSING HEART ACTIVITY

[75] Inventor: John B. Murphy, West Roxbury, Mass.

[73] Assignee: Hewlett-Packard Company, Palo Alto, Calif.

[21] Appl. No.: 838,501

[22] Filed: Oct. 3, 1977

[51] Int. Cl.² A61B 5/04

[52] U.S. Cl. 128/2.06 E; 128/418; 128/DIG. 4

[58] Field of Search 128/2.06 E, 2.1 E, 404, 128/418, 419 P, DIG. 4

[56] References Cited

U.S. PATENT DOCUMENTS

3,416,534	12/1968	Quinn	128/418
3,750,650	8/1973	Rutgers	128/2.06 E
3,827,428	8/1974	Hon et al.	128/2.06 E
3,986,497	10/1976	Dali	128/2.06 E
4,000,745	1/1977	Goldberg	128/418

FOREIGN PATENT DOCUMENTS

1316072 5/1973 United Kingdom 128/DIG. 4
1457426 12/1976 United Kingdom 128/2.06 E

OTHER PUBLICATIONS

Hon et al., "Electronic . . . Fetal Heart Rate", Ob. & Gyn., vol. 40, No. 3, Sep. 1972, pp. 362-365.

Primary Examiner—Lee S. Cohen

Attorney, Agent, or Firm—Stephen P. Fox

[57] ABSTRACT

An electrode assembly for sensing heart activity from body tissue includes a flexible guide tube, a spiral retaining coil disposed in one end of the guide tube, a handle disposed at the other end of the guide tube, and twisted wires inside the tube interconnecting the retaining coil and the handle. Rotation of the handle rotates the twisted wires, which in turn rotate the retaining coil to screw it into body tissue. Thereafter, the guide tube and handle are disengaged from the retaining coil and wires. A safety stop releasably disposed on the guide tube limits the rotation of the retaining coil and thus limits its depth of penetration into the body tissue.

32 Claims, 8 Drawing Figures

